

LUPES® SQUARE

APPLICATIONS

General Working Line
Purse Seine Line
Trawl/Bridle Line
Other Fishing Line

BENEFITS / FEATURES

Does not Harden
Does not Kink
Soft Hand
Durable
High Breaking Load
Easy to Splice
Excellent Abrasion Resistance



SPECIFICATIONS

Material	: 100% HT Polyester Fiber
Type	: L
Specific Gravity	: 1,38 kg/dm³
Construction	: 8 Strand Plaited (4x2)
UV Resistance	: Excellent
Chemical Resistance	: Good
Melting Point	: 265°C
Critical Temperature	: 170°C
Elongation At Break	: Approx. %15-20
Fiber Water Absorption	: Approx. %1-2
Wet Abrasion	: Good
Dry Abrasion	: Good
Standard	: EN ISO 1141
Length	: 100-200 m Wooden Spool or Coil

Other Colours on Request

DIA (mm)	Weight (kg/100m)	Min. B.Load (kgf)	DIA (inch)	Weight (lbs/100ft)	Min. B.Load (lbs)
12	10,90	2.875	1/2"	7,32	6.325
14	14,90	3.875	9/16"	10,01	8.525
16	19,40	5.000	5/8"	13,04	11.000
18	24,60	6.250	3/4"	16,53	13.750
20	30,40	8.250	13/16"	20,43	18.150
22	36,70	10.000	7/8"	24,66	22.000
24	43,70	11.500	1"	29,37	25.300
26	51,20	13.500	1-1/16"	34,41	29.700
28	59,50	15.500	1-1/8"	39,98	34.100
30	68,30	17.500	1-1/4"	45,90	38.500
32	77,70	20.000	1-5/16"	52,21	44.000
34	88,00	22.500	1 3/8"	59,14	49.500
36	98,40	25.000	1-1/2"	66,12	55.000
38	109,70	29.000	1 9/16"	73,72	63.800
40	121,00	33.000	1-5/8"	81,31	72.600

*Unspliced Break Load (All tests are in Accordance with ISO 2307)



CLASSIC
LOOK



LUPES® VIPERA

APPLICATIONS

Dock Line
Anchor Line
Towing Line

See Page 74

BENEFITS / FEATURES

Does not Harden
Does not Kink
Soft Hand
Durable
Flexible Cover
High Breaking Load
Excellent Abrasion Resistance



SPECIFICATIONS

Material	:	100% HT Polyester Fiber
Type	:	-
Specific Gravity	:	1,38 kg/dm³
Construction	:	Cover: 16-20-24 Plaited Core: 16 Plaited
UV Resistance	:	Excellent
Chemical Resistance	:	Good
Melting Point	:	256°C
Critical Temperature	:	170°C
Elongation at Break	:	Approx. %15
Fiber Water Absorption	:	Approx. %1-2
Wet Abrasion	:	Good
Dry Abrasion	:	Good
Standart	:	EN ISO 10547
Length	:	100-200 m Plastic/Wooden Spool or Coil

Other Colours on Request

DIA (mm)	Weight (kg/100m)	Min. B.Load (kgf)	DIA (inch)	Weight (lbs/100ft)	Min. B.Load (lbs)
8	4,85	1.320	5/16"	3,26	2.904
10	7,45	2.050	3/8"	5,01	4.510
12	11,00	2.900	1/2"	7,39	6.380
14	14,80	3.910	9/16"	9,95	8.602
16	19,40	5.070	5/8"	13,04	11.154
18	24,80	6.370	3/4"	16,67	14.014
20	30,40	7.800	13/16"	20,43	17.160
22	36,85	9.380	7/8"	24,76	20.636
24	43,65	11.110	1"	29,33	24.442
26	51,25	14.385	1-1/16"	34,44	31.647
28	59,40	16.630	1-1/8"	39,93	36.586

*Unspliced Break Load (All Tests are in Accordance with ISO 2307)



LUPES® VIPERA ► MOORING LINES

CLASSIC
LOOK

